



香港中文大學
The Chinese University of Hong Kong

7.7 Separation of Source and Channel Coding

A Separation Theorem

A Separation Theorem


- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .

A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.

A Separation Theorem


- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < R_c < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < \underline{R_c} < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$H < R_s < \underline{R_c} < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that


$$\underline{H < R_s} < \underline{R_c} < C.$$



A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that

$$\underline{H < R_s} < \underline{R_c} < C.$$




A Separation Theorem

- Consider transmitting an information source with entropy rate H reliably through a DMC with capacity C .
- If $H < C$, this can be achieved by separating source and channel coding without using feedback.
- Specifically, choose R_s and R_c such that

$$H < R_s < R_c < C.$$

- It can be shown that even with complete feedback, reliable communication is impossible if $H > C$. See textbook for details.



The [separation theorem for source and channel coding](#) has the following engineering implications:

The [separation theorem for source and channel coding](#) has the following engineering implications:

- asymptotic optimality can be achieved by separating source coding and channel coding

The [separation theorem for source and channel coding](#) has the following engineering implications:

- asymptotic optimality can be achieved by separating source coding and channel coding
- the source code and the channel code can be designed separately without losing asymptotic optimality

The [separation theorem for source and channel coding](#) has the following engineering implications:

- asymptotic optimality can be achieved by separating source coding and channel coding
- the source code and the channel code can be designed separately without losing asymptotic optimality
- only need to change the source code for different information sources

The [separation theorem for source and channel coding](#) has the following engineering implications:

- asymptotic optimality can be achieved by separating source coding and channel coding
- the source code and the channel code can be designed separately without losing asymptotic optimality
- only need to change the source code for different information sources
- only need to change the channel code for different channels

The [separation theorem for source and channel coding](#) has the following engineering implications:

- asymptotic optimality can be achieved by separating source coding and channel coding
- the source code and the channel code can be designed separately without losing asymptotic optimality
- only need to change the source code for different information sources
- only need to change the channel code for different channels

Remark For finite block length, the probability of error generally can be reduced by using joint source-channel coding.